

Package: subrank (via r-universe)

October 3, 2026

Type Package
Title Computes Copula using Ranks and Subsampling
Version 0.9.9.3
Date 2023-04-06
Author Jerome Collet
Maintainer Jerome Collet <jeromepcollet@gmail.com>
Description Estimation of copula using ranks and subsampling. The main feature of this method is that simulation studies show a low sensitivity to dimension, on realistic cases.
License GPL (>= 3)
LazyLoad yes
NeedsCompilation yes
Repository <https://jeromepcollet.r-universe.dev>
Date/Publication 2023-04-05 16:50:05 UTC
RemoteUrl <https://github.com/cran/subrank>
RemoteRef HEAD
RemoteSha 132fc7a1b9dbe3c9b54d52ad0212d3dca5f805d4

Contents

subrank-package	2
corc	3
corc0	4
desscop	5
desscoptous	6
estimdep	7
predictdep	8
predonfly	9
simany	11
simnul	12
Index	14

subrank-package

Computes Copula using Ranks and Subsampling

Description

Estimation of copula using ranks and subsampling. The main feature of this method is that simulation studies show a low sensitivity to dimension, on realistic cases.

Details

The DESCRIPTION file:

```
Package:      subrank
Type:         Package
Title:        Computes Copula using Ranks and Subsampling
Version:      0.9.9.3
Date:         2023-04-06
Author:       Jerome Collet
Maintainer:   Jerome Collet <jeromepcollet@gmail.com>
Description:  Estimation of copula using ranks and subsampling. The main feature of this method is that simulation studies show a low sensitivity to dimension, on realistic cases.
License:      GPL (>= 3)
LazyLoad:     yes
NeedsCompilation: yes
```

Index of help topics:

corc	Function to estimate copula using ranks and sub-sampling
corc0	Function to estimate copula using ranks and sub-sampling, minimal version.
desscop	Discrete copula graph, a two-dimensional projection
desscoptous	Discrete copula graph, ALL two-dimensional projections
estimdep	Dependence estimation
predictdep	Probability forecasting
predonfly	Probability forecasting
simany	Test statistic distribution under any hypothesis
simnul	Test statistic distribution under independence hypothesis
subrank-package	Computes Copula using Ranks and Subsampling

Taking a sample, its dimension, and a sub-sample size, allows to estimate a discretized copula. This object has interesting features: convergence to copula, robustness with respect to dimension.

Author(s)

Jerome Collet

Maintainer: Jerome Collet <jeromepcollet@gmail.com>

Examples

```
lon <- 31
a <- 2.85
x <- rnorm(lon)
y = a*x^2+rnorm(lon)
tablo = as.data.frame(cbind(x,y))
c=corc(tablo,c(1,2),8)
desscop(c,1,2)
```

corc

*Function to estimate copula using ranks and sub-sampling***Description**

Takes a sample, its dimension, a sub-sample size, and returns a discrete copula.

Usage

```
corc(dataframe, varnames, subsampsize, nbsafe=5,mixties=FALSE,nthreads=2)
```

Arguments

dataframe	a data frame, containing the observations
varnames	the name of the variables we want to estimate the dependence between
subsampsize	the sub-sample size
nbsafe	the ratio between the number of sub-samples and the cardinality of the discretized copula.
mixties	if TRUE, put equal weight on tied values, using random permutations
nthreads	number of number of threads, assumed to be strictly positive. For "full throttle" computations, consider using <code>parallel::detectCores()</code>

Value

cop	an array representing the discretized copula
ties	the number of sub-samples with a tie
nsubsampreal	the effective number of sub-samples drawn
varnames	the name of the variables studied
nnm	the number of observations without missing values

Author(s)

Jerome Collet

Examples

```
lon <- 30
a <- 2
x <- rnorm(lon)
y = a*x^2+rnorm(lon)
datatable = as.data.frame(cbind(x,y))
c=corc(datatable,c("x","y"),8)
c
sum(c$cop)
```

corc0	<i>Function to estimate copula using ranks and sub-sampling, minimal version.</i>
-------	---

Description

Minimal version of function corc.

Usage

```
corc0(datavector,sampsize,dimension,subsampsize,nboot,u,mixties=FALSE,nthreads=2)
```

Arguments

datavector	a vector, containing the observations
sampsize	the sample size
dimension	the sample dimension
subsampsize	the sub-sample size
nboot	the number of sub-samples (must be big)
u	a random seed, integer
mixties	if TRUE, put equal weight on tied values, using random permutations
nthreads	number of number of threads, assumed to be strictly positive. For "full throttle" computations, consider using <code>parallel::detectCores()</code>

Value

the number of hits for each vector of ranks, plus 2 last values of the vector : number of ties and number of sub-samples really used.

Author(s)

Jerome Collet

Examples

```
lon <- 30
a <- 2.85
x <- rnorm(lon)
y = a*x^2+rnorm(lon)
c=corc0(c(x,y),lon,2,8,1e5,75014)
c

c0=c(
1203, 1671, 1766, 959, 1586, 1715, 1803, 1205, 1260,1988, 2348, 1917, 3506, 2045, 1340,
1093, 2694, 2757,2233, 1085, 2322, 1793, 1569, 1263, 1709, 1747, 1512,1308, 1778, 1354,
1184, 1097, 2487, 2730, 2112, 1100,2435, 2033, 1572, 1093, 1369, 1722, 1462, 1015, 1228,
1419, 1776, 1852, 1009, 1097, 1179, 1323, 1595, 1316,1477, 2628, 889, 1178, 1981, 4000,
35, 840, 2091, 4467,0, 27405)
set.seed(75013)
lon=30
dimension=3
sssize=4
c0==corc0(rnorm(lon*dimension),lon,dimension,sssize,1e5,75014)
```

desscop

*Discrete copula graph, a two-dimensional projection***Description**

Draws a discrete joint probability, for 2 variables, using bubbles

Usage

```
desscop(copest, xname, yname, normalize = FALSE, axes = TRUE)
```

Arguments

copest	the estimated copula (the whole structure resulting from corc)
xname	the name of the variable we want to put on the horizontal axis
yname	the name of the variable we want to put on the vertical axis
normalize	if TRUE, the smallest probability is rescaled to 0, and the largest to 1
axes	if TRUE, puts the name of the variables on the axes

Author(s)

Jerome Collet

Examples

```
lon <- 31
a <- 2.85
x <- rnorm(lon)
y = a*x^2+rnorm(lon)
tablo = as.data.frame(cbind(x,y))
c=corc(tablo,c("x","y"),8)
desscop(c,"x","y")

tablo = as.data.frame(cbind(x=rep(0,each=lon),y=rep(0,each=lon)))
c=corc(tablo,c("x","y"),8,mixties=TRUE)
desscop(c,"x","y")
```

desscoptous

Discrete copula graph, ALL two-dimensional projections

Description

Draws a discrete joint probability, for 2 variables, using bubbles

Usage

```
desscoptous(copest, normalize = FALSE)
```

Arguments

copest	the estimated copula (the whole structure resulting from corc)
normalize	if TRUE, the smallest probability is rescaled to 0, and the largest to 1

Author(s)

Jerome Collet

Examples

```
lon <- 31
a <- 2.85
x <- rnorm(lon)
y = a*x^2+rnorm(lon)
z = rnorm(lon)
tablo = as.data.frame(cbind(x,y,z))
c=corc(tablo,c("x","y","z"),8)
desscoptous(c)
```

estimdep	<i>Dependence estimation</i>
----------	------------------------------

Description

From a set of observations, builds a description of the multivariate distribution

Usage

```
estimdep(dataframe, varnames, subsampsize, nbsafe=5, mixties=FALSE, nthreads=2)
```

Arguments

dataframe	a data frame containing the observations
varnames	the name of the variables we want to estimate the multivariate distribution
subsampsize	the sub-sample size
nbsafe	the ratio between the discretized copula size and the number of sub-samples
mixties	if TRUE, put equal weight on tied values, using random permutations
nthreads	number of number of threads, assumed to be strictly positive. For "full throttle" computations, consider using <code>parallel::detectCores()</code>

Value

the description of the dependence, it is an object with the following parts:

cop	the array representing the discretized copula
margins	the matrix representing the margins, estimated using kernel density estimation
varnames	the names of the variables

Author(s)

Jerome Collet

Examples

```
lon=3000
plon=3000
subsampsize=20

#####
x=(runif(lon)-1/2)*3
y=x^2+rnorm(lon)
z=rnorm(lon)
donori=as.data.frame(cbind(x,y,z))
depori=estimdep(donori,c("x","y","z"),subsampsize)

knownvalues=data.frame(z=rnorm(plon))
```

```

prev <- predictdep(knownvalues,depori)
plot(prev$x,prev$y,xlim=c(-2,2),ylim=c(-2,5),pch=20,cex=0.5)
points(donori[,1:2],col='red',pch=20,cex=.5)

knownvalues=data.frame(x=(runif(100)-1/2)*3)
prev <- predictdep(knownvalues,depori)
plot(prev$x,prev$y,xlim=c(-2,2),ylim=c(-2,5),pch=20,cex=0.5)
points(donori[,1:2],col='red',pch=20,cex=.5)

knownvalues=data.frame(y=runif(100,min=-2,max=4))
prev <- predictdep(knownvalues,depori)
plot(prev$x,prev$y,xlim=c(-2,2),ylim=c(-2,5),pch=20,cex=0.5)
points(donori[,1:2],col='red',pch=20,cex=.5)

```

predictdep

Probability forecasting

Description

From a set of incomplete observations, and a description of the dependence, provides simulated values of the unknown coordinates. It is also possible to simulate unconditionally, with empty observations.

Usage

```
predictdep(knownvalues,dependence,smoothing=c("Uniform","Beta"),nthreads=2)
```

Arguments

knownvalues	in case of conditional simulation, a matrix containing incomplete observations, the known coordinates being the same for all observations. If no variable name in knownvalues appears in dependence\$varnames, then the simulation is unconditional.
dependence	the description of the dependence we want to use to forecast, as built by function estimdep
smoothing	the smoothing method for input and output ranks.
nthreads	number of number of threads, assumed to be strictly positive. For "full throttle" computations, consider using <code>parallel::detectCores()</code>

Value

the matrix of the completed observations

Author(s)

Jerome Collet

Examples

```

lon=100
plon=100
subsampsize=10

shift=0
noise=0
knowndims=1

x=rnorm(lon)
y=2*x+noise*rnorm(lon)
donori=as.data.frame(cbind(x,y))
depori=estimdep(donori,c("x","y"),subsampsize)
##
knownvalues=data.frame(x=rnorm(plon)+shift)
prev <- predictdep(knownvalues,depori)
##
plot(prev$x,prev$y,xlim=c(-2,2),ylim=c(-2,5),pch=20,cex=0.5)
points(donori[,1:2],col='red',pch=20,cex=.5)
##
knownvalues=data.frame(x=rnorm(plon)+shift)
prev <- predictdep(knownvalues,depori,smoothing="Beta")
##
plot(prev$x,prev$y,xlim=c(-2,2),ylim=c(-2,5),pch=20,cex=0.5)
points(donori[,1:2],col='red',pch=20,cex=.5)

# souci normal si |shift|>>1

knownvalues=data.frame(z=rnorm(plon)+shift)
prev <- predictdep(knownvalues,depori)
##
plot(prev$x,prev$y,xlim=c(-2,2),ylim=c(-2,5),pch=20,cex=0.5)
points(donori[,1:2],col='red',pch=20,cex=.5)

```

predonfly

Probability forecasting

Description

From two sets of observations, first one of complete observations and second one of incomplete observations, provides simulated values of the unknown coordinates.

Usage

```

predonfly(completeobs,incompleteobs,varnames,subsampsize,nbpreds=1,mixties=FALSE,
          maxtirs=1e5,complete=TRUE,nthreads=2)

```

Arguments

<code>completeobs</code>	the set of complete observations.
<code>incompleteobs</code>	the set of incomplete observations.
<code>varnames</code>	the modeled variables.
<code>subsampsize</code>	the sub-sample size.
<code>nbpreds</code>	the number of predictions for each incomplete observation.
<code>mixture</code>	if TRUE, should put equal weight on tied values, using random permutations (not yet implemented)
<code>maxtirs</code>	the maximum number of sub-samples, to stop the computation even if they did not provide <code>nbpreds</code> predictions for each incomplete observation.
<code>complete</code>	If TRUE, predictions are completed with incomplete observations
<code>nthreads</code>	number of number of threads, assumed to be strictly positive. For "full throttle" computations, consider using <code>parallel::detectCores()</code>

Value

the matrix of the completed observations

Author(s)

Jerome Collet

Examples

```
lon=100
plon=30
subsampsize=10

x=rnorm(lon)
y=2*x+rnorm(lon)*0
donori=as.data.frame(cbind(x,y))
##
knownvalues=data.frame(x=rnorm(plon))
prev <- predonfly(donori,knownvalues,c("x","y"),subsampsize,100)

##
plot(prev$x,prev$y,pch=20,cex=0.5,
      ylim=range(c(prev$y,donori$y),na.rm=TRUE),xlim=range(c(prev$x,donori$x)))
points(donori[,1:2],col='red',pch=20,cex=.5)

lon=3000
mg=20
dimtot=4
rayon=6

genboules <- function(lon,a,d)
{
  ss <- function(vec)
```

```

    {return(sum(vec*vec))}
    surface=matrix(nrow=lon,ncol=d,data=rnorm(lon*d))
    rayons=sqrt(apply(surface,1,ss))
    surface=surface/rayons
    return(matrix(nrow=lon,ncol=d,data=rnorm(lon*d))+a*surface)
}

#####

donori=genboules(lon,rayon,dimtot)
donori=as.data.frame(donori)

dimconnues=3:dimtot
valconnues=matrix(nrow=1,ncol=length(dimconnues),data=0)
valconnues=as.data.frame(valconnues)
names(valconnues)=names(donori)[3:dimtot]
prev <- predonfly(donori,valconnues,names(donori),subsampsize,100)

boule2=genboules(plon,rayon,2)

plot(boule2[,1:2],xlab='X1',ylab='X2',pch=20,cex=.5)
plot(prev$V1,prev$V2,xlab='X1',ylab='X2',pch=20,cex=.5)

```

simany

Test statistic distribution under any hypothesis

Description

Simulates the test statistic, under independence

Usage

```
simany(sampsize,dimension,subsampsizes,sampnum,nbsafe=5,nthreads=2, fun=NULL, ...)
```

Arguments

sampsize	sample size
dimension	sample dimension
subsampsizes	vector of sub-sample sizes
sampnum	number of samples
nbsafe	the ratio between the number of sub-samples and the cardinality of the discretized copula.
nthreads	number of number of threads, assumed to be strictly positive. For "full throttle" computations, consider using <code>parallel::detectCores()</code>
fun	the function describing the dependence.
...	optional arguments to fun

Value

lrs	the distances with independent case
lrs2mean	the distances with theoretical value, given dependence fun
scarcities	the proportions of non-reached vector ranks
DistTypes	a recall of the list of the distance types: "KL","L2","L1","APE"

Author(s)

Jerome Collet

Examples

```
depquad <- function(lon,dd,a)
{
  x <- rnorm(lon)
  y0 <- a*x^2
  y <- y0 + rnorm(lon)
  reste=rnorm((dd-2)*lon)
  return(c(x,y,reste))
}
sims0=simany(101,3,8,50,nbsafe=1)
seuils=apply(sims0$lrs,3,quantile,0.95)
seuils=matrix(ncol=4,nrow=50,seuils,byrow=TRUE)
sims1=simany(101,3,8,50,nbsafe=1,fun=depquad,a=0.5)
apply(sims1$lrs[,1,]>seuils,2,mean)
```

simnul	<i>Test statistic distribution under independence hypothesis</i>
--------	--

Description

Simulates the test statistic, under independence

Usage

```
simnul(sampsize, dimension, subsampsizes, sampnum,KL=TRUE,nbsafe=5,nthreads=2)
```

Arguments

sampsize	sample size
dimension	sample dimension
subsampsizes	vector of sub-sample sizes
sampnum	number of samples
KL	if TRUE, returns the Kullback-Leibler divergence with the independent case, if FALSE, the L2 distance. There is no re-normalization, contrary to what happens for simany.

nbsafe	the ratio between the number of sub-samples and the cardinality of the discretized copula.
nthreads	number of number of threads, assumed to be strictly positive. For "full throttle" computations, consider using <code>parallel::detectCores()</code>

Value

lrs	the distances with independent case
scarcities	the proportions of non-reached vector ranks

Author(s)

Jerome Collet

Examples

```
library(datasets)
# plot(swiss)
c=corc(swiss,1:3,8)
c
RV=sum(c$cop*log(c$cop),na.rm=TRUE)+3*log(8)
sims=simnul(47,3,8,100)
pvalue=mean(RV<sims$lrs)
pvalue
RV
summary(sims$lrs)
```

Index

corc, [3](#), [5](#), [6](#)

corc0, [4](#)

desscop, [5](#)

desscoptous, [6](#)

estimdep, [7](#), [8](#)

predictdep, [8](#)

predonfly, [9](#)

simany, [11](#)

simnul, [12](#)

subrank (subrank-package), [2](#)

subrank-package, [2](#)